

# ULTIMATE LUBER™

## **Automatic Lubricator**

The **ULTIMATE LUBER**<sup>™</sup> is a powerful, motor-driven automatic lubricator which is refillable using standard grease guns. Its microprocessor controlled, energy efficient motor delivers grease to a fixed displacement pump which produces pressures up to **900psi**. This strength allows the **ULTIMATE LUBER**<sup>™</sup> to drive lubricant through long feed lines and to cycle progressive distributors to feed several bearings consecutively. When a dispensing cycle is selected, the units will activate at programmed intervals. At each interval, the **ULTIMATE LUBER**<sup>™</sup> dispenses approximately 1.25cc of grease. Neither temperature nor altitude will affect the lubricant output.



### **Features**

- Most powerful lubricator on the market. Produces up to 900psi which enables it to service single-point applications up to 30' away (9m.) and multi-point applications up to 20' (6m.) away.
- Available with long-life replaceable battery packs or optional external power sources. (AC and DC)
- Available in 3 sizes: 4, 8, or 17 oz. (125, 250 or 500cc)
- Single or Multi-point configuration.
- · Refillable using a standard grease gun.
- Able to service up to 12 lube points with optional progressive distribution block.

- Optional remote control available to connect to customer equipment or machinery. (eg. PLC, contactors, relays)
- Suitable for indoor/outdoor use.
- Multiple settings from 15 days to 2 years to empty.
- Optional easy to install mounting plates for both single or multi-point applications available.
- Designed for the industrial workplace
- dust proof
- weather-resistant

#### Temperature Range:

5°F to +132°F (-15°C to +55°C) (NOTE: Low Temp lubricants must be used at low temperatures)

#### Size:

Model 500: 8-3/4" high X 4-3/4" dia.

Model 250: 7-1/2" high X 4" dia.

Model 125: 7-1/2" high X 3-1/8" dia.





