

Proven Applications by Thousands of Companies . . .

Stacker Cranes
Bridge Cranes
Shakers
Agitators
Ways
Elevators
Roof Fans
Farm Machinery
Hoists
Heat Treat Furnaces
HVAC
Coal Handling Equipment
Conveyors (Drives take-ups and idlers)
Electric Motors
Mobile Equipment
Laundry Operations
Presses
All Production Equipment
Automatic Welders
Mining - Surface & Underground
Waste Treatment Systems
All Pumps
Oil & Gas
Refineries
Pulp & Paper - Lumber Mills
Chain Lubrication

ACCESSORIES



We also sell accessories to help you get the most out of your lubricator.

- Clamps
- Distribution blocks - 2, 3, 4, 6, 8 port
- Weatherproof caps (optional)
- Nylon hose
- Brushes
- Various adaptors
- Programmable options (MD & Ultimate series)
- Accessories for remote power & control options

Represented by:

Manufactured by:

A.T.S. ELECTRO-LUBE INTERNATIONAL INC.
7388 Wilson Ave, Delta, BC Canada V4G 1H3
TOLL FREE 1-800-663-8141
TOLL FREE FAX 1-800-663-8140
www.atselectrolube.com

The World's Champion Lubricator



Single Point
Automatic Lubricator

Continuous Lubrication
24/7



Motor Driven

Customer
Refillable

Single or
Multipoint
Lubrication

A.T.S. ELECTRO-LUBE

OVER 25 YEARS OF MANUFACTURING
RELIABLE LUBRICATION PRODUCTS FOR
AN INDUSTRIAL WORLD

ELECTRO-LUBER MD™ 2000

MOTOR-DRIVEN LUBRICANT DISPENSER-200 PSI



ELECTRO-LUBER

ORIGINAL AUTOMATIC LUBRICATOR



ULTIMATE SERIES

MOTOR DRIVEN LUBRICANT DISPENSER-900 PSI



FEATURES	Customer programming available	Continuous lubrication	Customer programming available
SIZES	500cc, 250cc, 125cc	500cc, 250cc, 125cc, 60cc	500cc, 250cc, 125cc
TECHNOLOGY	Mechanical progressive pump	Safe inert Nitrogen gas	Mechanical fixed displacement pump
PRESSURE RANGE	Up to 200 psi	Up to 50 psi	Up to 900 psi
TEMPERATURE RANGE	+14°F to 131°F (-10°C to +55°C)	-40°F to 131°F (-40°C to +55°C)	+14°F to 131°F (-10°C to +55°C)
DISPENSING RATES	Variable to 2 year	Variable to 1 year	Variable to 2 year
REUSABILITY	Refillable	Remove & replace (re & re)	Refillable
DIAGNOSTICS	Dual color LED	Single color LED	Tri color LED
OPTIONS	Remote control	Remote control or remote power	Remote control
POWER SOURCE	Battery pack, DC Power (10 to 30 VDC), AC Power (120 VAC to 6 VDC)	Sealed, nonreplaceable batteries	Battery pack, DC Power (10 to 30 VDC), AC Power (120 VAC to 6 VDC)
APPROVALS	Pending	CSA, UL, Instrinsically Safe Class 1, Groups A, B, C, D, E, F, G, MSHA, Energy Mines	Pending

Advantages of Electro-Lube Lubrication:

- Versatile lubricant selection
- Units can be filled with either oil or grease
- 24/7 reliability
- Continuous lubrication
- Economical multipoint systems

- Filled with customer specified lubricant
- Original units have easy change out (remove & replace)
- Visual lubricant level indication
- Indicator lights

- Installed in any orientation
- Weatherproof
- Labour cost reduction
- Improve productivity
- Custom programmable available
- Made from premium nylon
 - able to resist machine vibration